Refine Search

Search Results -

Terms	Documents
L21 and L20	0

Database:

> US Pre-Grant Publication Full-Text Database
> US Patents Full-Text Database
> US OCR Full-Text Database
> EPO Abstracts Database
> JPO Abstracts Database
> Derwent World Patents Index
> IBM Technical Disclosure Bulletins

Search:

> L22

[Refine Search]

[Recall Text] [Clear] [Interrupt]

Search History

DATE: Thursday, September 30, 2004   Printable Copy   Create Case

Set Name side by side	Query	Hit Count	Set Name result set
DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ			
L22	L21 and l20	0	L22
L21	security state	414	L21
L20	L19 and l3	5	L20
L19	L18 and l2	5	L19
L18	L17 and l16	6	L18
L17	client service	2439	L17
L16	l15 and l13	54	L16
L15	l1 near l5	13113	L15
L14	l12 same l11	27	L14
L13	L12 and l11	253	L13
L12	client type	929	L12
L11	client request	9150	L11
L10	request	410387	L10
L9	L8 and l7	10591	L9

L8	network	930252	L8
L7	L6 and l4	13553	L7
L6	11 same l5	27507	L6
L5	level	3040354	L5
L4	l3 same l1	46517	L4
L3	access	1212723	L3
L2	authentication	52043	L2
L1	security	230333	L1

END OF SEARCH HISTORY

Google

client type, client request, authentication | Search | Advanced Search
Preferences

Web   Results 1 - **10** of about **545,000** for <u>client type</u>, <u>client request</u>, <u>authentication</u>. (**0.24** seconds)

<u>Client authentication</u>: IBM HTTP Server
... **authentication** level and the access control **type**, along with ... choose the Required
level of **client authentication**, the secure server **requests** a certificate ...
www-3.ibm.com/software/webservers/ httpservers/doc/v1326/manual/ibm/9accauth.htm - 11k -
<u>Cached</u> - <u>Similar pages</u>

<u>Client</u> Detection Service
... must first be successfully authenticated, browser **type client** detection is accomplished
within the **Authentication** Service. When a **client's request** is passed ...
docs.sun.com/source/816-6774-10/prog_cdm.html - 27k - <u>Cached</u> - <u>Similar pages</u>

Sun ONE Identity Server Programmer's Guide: Chapter 11 **Client** ...
... **type** using information stored in the HTTP string **request**. ... this information to retrieve
the browser **type's** characteristics ... and are referred to as the **client** data ...
docs.sun.com/source/816-6687-10/cdm.html - 44k - <u>Cached</u> - <u>Similar pages</u>
[<u>More results from docs.sun.com</u>]

Microsoft ISA Server 2000 **Client Types**
... can pass all Hypertext Transfer Protocol (HTTP) **requests** to the Web ... protocol usage,
destination, and content **type** are also applied to SecureNAT **clients**.). ...
www.microsoft.com/technet/ Security/prodtech/isa/isafp1/isasct.mspx - 33k - <u>Cached</u> - <u>Similar pages</u>

IAS **Authentication Clients** Object; Windows Server 2003 Deployment ...
... Counter Name, Description, Counter **Type**. ... which RADIUS Access-Reject packets were
sent to this **client**. ... Access-**Requests**, Shows the number of packets received on the ...
www.microsoft.com/resources/documentation/ WindowsServ/2003/all/deployguide/en-
us/counters1_izun.asp - 14k - <u>Cached</u> - <u>Similar pages</u>
[<u>More results from www.microsoft.com</u>]

<u>Client</u>-side Access Restriction using VeriSign Digital ID's and ...
... If a **client** certificate is not already present on the session ... is absent, the function
is applied to all **requests**. ... a user name, the values of auth-**type**, auth-user ...
www.verisign.com/repository/**client**auth/ent_ig.htm - 45k - <u>Cached</u> - <u>Similar pages</u>

<u>Understanding ISA's different **Authentication types**.</u>
... when dabbling with this **type** of **authentication**. ... is when ISA Server passes a **client's**
authentication information to ... for both outgoing and incoming Web **requests**. ...
www.isaserver.org/tutorials/Understanding_ ISAs_different_Authentication_types.html - 37k - Sep 29, 2004 -
<u>Cached</u> - <u>Similar pages</u>

<u>Web-Access **Authentication** Using RADIUS - CISSP Network Security ...</u>
... The accounting protocol supports two **types** of packets, accounting-**request** and accounting ...
between the RADIUS accounting server and **client** are protected ...
www.infoseceng.com/radius.htm - 16k - <u>Cached</u> - <u>Similar pages</u>

<u>IBM HTTP Server help</u>: **Client authentication**
... the secure server does not **request** certificates from ... of access control based on **client**
certificate information. The **type** is set with the SSLFakeBasicAuth or ...
web33.evenue.net/manual/ibm/9accauth.htm - 8k - <u>Cached</u> - <u>Similar pages</u>

Authentication Operations
... The auth_forward option specifies the **authentication type** to be used ... by the **client**
for the **client** to server ... that this is an **authentication request** the printer ...
www.lprng.com/LPRng-Reference-Multipart/auth.htm - 13k - Sep 29, 2004 - Cached - Similar pages

Goooooooooogle ▶

Result Page: **1** 2 3 4 5 6 7 8 9 10   **Next**

Free! Get the Google Toolbar. Download Now - About Toolbar

Google ▾   Search Web ▾   49 Pop-ups blocked   News   AutoFill

client type, client request, authen   Search

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve

Google Home - Advertising Programs - Business Solutions - About Google

©2004 Google

IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE

IEEE

Membership   Publications/Services   Standards   Conferences   Careers/Jobs

IEEE *Xplore*

Welcome
United States Patent and Trademark Office

Help   FAQ   Terms   IEEE Peer Review   **Quick Links** ▼   » Se

Welcome to IEEE *Xplore*

○ Home
○ What Can
   I Access?
○ Log-out

Tables of Contents

○ Journals
   & Magazines
○ Conference
   Proceedings
○ Standards

Search

○ By Author
○ Basic
○ Advanced

Member Services

○ Join IEEE
○ Establish IEEE
   Web Account
○ Access the
   IEEE Member
   Digital Library

IEEE Enterprise

○ Access the
   IEEE Enterprise
   File Cabinet

🖳 Print Format

Your search matched **5** of **1075719** documents.
A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance
Descending** order.

Refine This Search:
You may refine your search by editing the current search expression or enter
new one in the text box.

| client <and> security level | **Search** |

☐ Check to search within this result set

Results Key:
JNL = Journal or Magazine   **CNF** = Conference   **STD** = Standard

---

1 **Integration of legacy client-server applications in a secure multi-tie
architecture**
Cotroneo, D.; Mazzeo, A.; Romano, L.; Russo, S.;
Parallel, Distributed and Network-based Processing, 2002. Proceedings. 10th
Euromicro Workshop on , 9-11 Jan. 2002
Pages:269 - 276

[Abstract]   [PDF Full-Text (366 KB)]   **IEEE CNF**

---

2 **Dynamic authentication for high-performance networked applicatio**
Schneck, P.A.; Schwan, K.;
Quality of Service, 1998. (IWQoS 98) 1998 Sixth International Workshop on ,
20 May 1998
Pages:127 - 136

[Abstract]   [PDF Full-Text (1212 KB)]   **IEEE CNF**

---

3 **Mobile agent middleware for mobile computing**
Bellavista, P.; Corradi, A.; Stefanelli, C.;
Computer , Volume: 34 , Issue: 3 , March 2001
Pages:73 - 81

[Abstract]   [PDF Full-Text (692 KB)]   **IEEE JNL**

---

4 **Fast server-aided secret computation protocols for modular
exponentiation**
Kawamura, S.; Shimbo, A.;
Selected Areas in Communications, IEEE Journal on , Volume: 11 , Issue: 5 ,
1993
Pages:778 - 784

[Abstract]   [PDF Full-Text (568 KB)]   **IEEE JNL**

5 **An implementation of MLS on a network of workstations using X.500/509**
Davis, J.; Jacobson, D.; Bridges, S.; Wright, K.;
Performance, Computing, and Communications Conference, 1997. IPCCC 199
IEEE International , 5-7 Feb. 1997
Pages:546 - 553

[Abstract]   [PDF Full-Text (564 KB)]   **IEEE CNF**

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account |
New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online
Publications | Help | FAQ| Terms | Back to Top